



### Overview

Model Name	APC Smart-UPS C 3000VA Rack mount LCD 230V
Includes	CD with software , Documentation CD , Installation guide , Rack Mounting brackets , USB cable
Standard Lead Time	Usually Ships within 2 Weeks
Product Distribution	Afghanistan , Algeria , Angola , Argentina , Armenia , Australia , Azerbaijan , Bahrain , Bangladesh , Belarus , Benin , Bhutan , Bolivia , Botswana , Brunei Darussalam , Burkina Faso , Burundi , Cambodia , Cameroon , Central African Republic , Chad , Chile , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , Cote D'Ivoire , Djibouti , East Timor , Egypt , Equatorial Guinea , Eritrea , Ethiopia , Falkland Islands (Malvinas) , Gabon , Gambia , Georgia , Ghana , Guadeloupe , Guinea , French Guiana , Hong Kong , Indonesia , Iran (Islamic Republic Of) , Iraq , Israel , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Lebanon , Lesotho , Liberia , Madagascar , Malawi , Mali , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , New Zealand , Niger , Nigeria , Oman , Pakistan , Papua New Guinea , Paraguay , Peru , Philippines , Qatar , Reunion , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Somalia , South Africa , Sri Lanka , Sudan , Suriname , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uruguay , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

### Output

Output Power Capacity	2100 Watts / 3000 VA
Max Configurable Power (Watts)	2100 Watts / 3000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Sine wave
Output Connections	(1) IEC 320 C19 (Battery Backup) , (2) IEC Jumpers (Battery Backup) , (8) IEC 320 C13 (Battery Backup)

### Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20
Input voltage range for main operations	180 - 287 V

## Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Replacement Battery	APCRBC151
RBC Quantity	1

## Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	--

## Surge Protection and Filtering

Surge energy rating	300 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	89.0 mm
Maximum Width	480.0 mm
Maximum Depth	670.0 mm
Rack Height	2 U
Net Weight	41.0 kg
Shipping Weight	50.9 kg
Shipping Height	254.0 mm
Shipping Width	600.0 mm
Shipping Depth	980.0 mm
Color	Black
Units per Pallet	16.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	42.000 dB
Online Thermal Dissipation	81.000 BTU/hr

## Conformance

Approvals	C-tick , CE , EAC , GOST , GS Mark , IRAM , SABS , VDE
Standard warranty	2 years repair or replace
Equipment protection policy	Lifetime : \$150000

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs